



SD9043AC

CIT RAIL

CIT Put Knowledge
to Work[®]

SD9043AC

CIT RAIL

Builder Model	EMD SD9043AC	
Nominal Dimensions	Length Between Couplers Distance Between Bolster Centers Height - Cab Roof to Top of Rail Truck Wheel Base	80' 2" 54' 2" 15' 8" 13' 7"
Main Components	16-710G3C-ES Prime Mover TA-22 Main Traction Alternator CCBII Airbrake	
Drive	Traction Motors Model Gear Ratio Wheel Diameter	6 1TB2830 83:16 45"
Weights and Capacities	Nominal Weight Fuel Tank Capacity Sand Cooling Water Lubricating Oil	426,000 lbs 5,800 gals 40 cu ft 320 gals 441 gals

Performance	Minimum Continuous Speed Continuous Tractive Effort Starting Tractive Effort Maximum Locomotive Speed	9.3 mph 147,000 lbs 185,000 lbs 75 mph
Horsepower	Engine Speed Tractive Horsepower	950 rpm 4,300
Build Date	1999-2000	
Additional Equipment	Air Conditioning AESS Ditch lights front and rear Distributed power Extended Range Dynamic Brakes Radial trucks Isolated cab Toilet	

CIT Rail
30 South Wacker Drive, Suite 2900
Chicago, IL 60606
www.cit.com

Mike Cleary
312.659.9516
mt.cleary@cit.com

Brian Ellison
724.301.3970
brian.ellison@cit.com